MT811X

Uni-polar, Hall-Effect Magnetic Position Sensor

1 Product Description

The MT811X family is produced by BCD technology with both high performance and high reliability. The Hall IC internally includes an on-chip Hall voltage generator, a voltage regulator for operation with supply voltage of 2.8V to 24V, a small-signal amplifier, Hall sensors with dynamic offset cancellation, a schmitt trigger and an open-drain output with over-current protection. It features temperature compensation technique to make the magnetic switching points stable over a wide temperature range. Other key features such as reverse supply voltage protection, output over-current protection and ESD level exceeding ±5.5KV (HBM) make the IC extremely robust and fault tolerant, which is important in demanding application environment such as automotive. Its extremely low operating supply voltage 2.8V also makes it possible to add external resistance in series with the supply pin for even greater protection against high voltage transients from the power supply.


When the magnetic flux density (B) is greater than the operating point (B_{OP}), the output turns on (Low). The output is held steady till the magnetic flux density (B) is less than the releasing point (B_{RP}), at which point it turns off (High).

2 Features

- BCD Technology
- Uni-polar Switch
- 2.8~24V Operating Vcc Range
- -40℃~150℃ Operating Temperature
- Package Option:
  Flat TO-92
  SOT-23
  SOT-23 (Thin Outline)
- Magnetic Sensitivity Option:
  B_{OP}=110Gs, B_{RP}=80Gs
- Open-Drain Output
- -27V Reversed Power Supply Protection
- Output Limiting Current Protection
- RoHS Compliant: (EU)2015/863

3 Product Overview of MT811X

Part No.	Description
MT8111A	Flat TO-92, bulk packaging (1000pcs/bag)
MT8111AT	SOT-23, tape & reel (3000pcs/bag)



4 Applications

- Home appliances
- Industrial
- Position Detection
- Proximity Switch

5. Pin Configuration and Functions

	Vcc	Out	GND
SOT-23	1	2	3
SOT-23 Thin Outline	1	2	3
Flat TO-92	1	3	2
Description	Power	Output Open-Drain	Ground




Figure 1 Pin Configuration & Functions

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

微信扫码咨询客服

Table of Contents

1 Product Description....1
2 Features....1
3 Product Overview of MT811X....1
4 Applications....1
5 Pin Configuration and Functions....1
6 Definition of Switching Function....3
7 Function Description....3
8 Feature Description....3
9 Functional Block Diagram....4
10 Electrical and Magnetic Characteristics....4
10.1 Absolute Maximum Ratings....4
10.2 Electrical Specifications....5
10.3 Magnetic Characteristics....5
10.4 ESD Ratings....5
10.5 Characteristic Performance....6
10.6 Typical Output Waveform....7
11 Typical Application Circuit....7
12 Package Material Information....8
12.1 SOT-23 Package Information....8
12.2 SOT-23 Thin Outline Package Information....9
12.3 Flat TO-92 Package Information....10
13 Copy Rights and Disclaimer....11

Reversion History

1	Originally Version	
2	1.1 Version	Update Magnetic Characteristics
3	1.2 Version	Update Electrical Specifications Update Copy Rights and Disclaimer
4	1.3 Version	Update the marking spec of SOT-23 & SOT-23 (Thin Outline)

6 Definition of Switching Function

Figure.2 & Figure.3 shows the device functionality and hysteresis




Figure.2 Switching Function Uni-polar (North)
SOT-23




Figure.3 Switching Function Uni-polar (South)
Flat TO-92 / SOT-23 (Thin Outline)

7 Function Description

B_{OP}: Operating Point, Magnetic flux density applied on the branded side of the package which turns the output driver ON (V_{OUT}=Low)

B_{RP}: Releasing Point, Magnetic flux density applied on the branded side of the package which turns the output driver OFF (V_{OUT}=High)

B_{HYST}: Hysteresis Window, $|B_{OP} - B_{RP}|$
Devices that have a lower magnetic threshold (V_{OUT}=High) detect magnets at a farther distance. Higher thresholds (V_{OUT}=Low) generally require a closer distance or larger magnet.

8 Feature Description

The MT811X device is sensitive to the magnetic field component that is perpendicular to the top of the package




Figure.4 Flux Direction Polarity

9 Functional Block Diagram




Figure.5 Functional Block Diagram

10 Electrical and Magnetic Characteristics

10.1 Absolute Maximum Ratings

Absolute maximum ratings are limited values to be applied individually, and beyond which the serviceability of the circuit may be impaired. Functional operability is not necessarily implied. Exposure to absolute maximum rating conditions for an extended period of time may affect device reliability.

Symbol	Parameters	Min	Max	Units
V_{CC}	Supply Voltage	-	27	V
V_{RCC}	Reverse Battery Voltage	-27	-	V
V_{OUT}	Output Voltage	-	27	V
I_{OUT}	Continuous Output Current	-	50	mA
T_A	Operating Ambient Temperature	-40	150	℃
T_S	Storage Temperature	-50	150	℃
T_J	Junction Temperature	-	165	℃
B	Magnetic Flux Density	No Limit		Gs

10.2 Electrical Specifications

At T_A=-40~150 ℃, V_{CC}=2.8V~24V (unless otherwise specified)

Symbol	Parameters	Test Condition	Min	Typ	Max	Unit
V_{CC}	Supply Voltage	Operating	2.8	-	24	V
I_{CC}	Supply Current	B<B_{OP}	-	3.50	6	mA
I_{OCP}	Short Circuit Protection Current	B>B_{OP}, V_{OUT}=V_{CC}	-	50	-	mA
V_{DSON}	Output Saturation Voltage	I_{OUT}=20mA, B>B_{OP}	-	-	0.4	V
I_{OFF}	Output Leakage Current	V_{OUT}=24V	-	-	10	uA
T_R	Output Rise Time	R_L=1KOhm, C_L=20pF	-	-	1.0	us
T_F	Output Fall Time	R_L=1KOhm, C_L=20pF	-	-	1.0	us
T_{PO}	Power on Time	dV_{CC}/dt>5V/uS B>$B_{OP(MAX)}$	-	-	25	us
F_C	Chopping Frequency		-	200	-	KHz
F_S	Sampling Frequency		-	100	-	KHz
R_{TH}	Thermal Resistance of SOT-23		-	301	-	℃/W
	Thermal Resistance of SOT-23 (Thin Outline)		-	301	-	℃/W
	Thermal Resistance of TO-92		-	230	-	℃/W

10.3 Magnetic Characteristics

At V_{CC}=2.8V~24V (unless otherwise specified)

Part No.	Symbol	Min	Typ	Max	Unit
MT8111 Series	B_{OP}, T_A =25℃	60	110	160	Gs
	B_{RP}, T_A =25℃	30	80	130	Gs
	B_{HYST}, T_A =25℃	10	30	50	Gs

10.4 ESD Ratings

Symbol		Reference	Values	Unit
V_{ESD}	Human-body model (HBM)	AEC-Q100-002	±5500	V
	Charged-device model (CDM)	AEC-Q100-011	±1000	V

10.5 Characteristic Performance

At V_{CC}=5V




Figure.6 Average Supply Current vs. Temperature




Figure.7 Magnetic Characteristics vs. Temperature (B_{OP} & B_{RP})




Figure.8 Magnetic Characteristics vs. Temperature (B_{HYST})

10.6 Typical Output Waveform

MT8111A as example




Figure.9 Digital Output vs. Magnetic Flux Density

11 Typical Application Circuit

MT8111AT as example
Note: Recommended value for R_L is 1KOhms to 10KOhms




Figure.10 Typical Application Circuit

12 Package Material Information (For Reference Only – Not for Tooling Use)

12.1 SOT-23 Package Information




Figure.11 SOT-23 Chip Marking Spec




Figure.12 SOT-23 Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0 °	8 °	0 °	8 °
x	1.460 TYP		0.057 TYP	
y	0.800 TYP		0.032 TYP	
z	0.600 TYP		0.024 TYP	

12.2 SOT-23 (Thin Outline) Package Information




Figure.13 SOT-23 (Thin Outline) Chip Marking Spec




Figure.14 SOT-23 (Thin Outline) Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e		0.950 TYP		0.037 TYP
e1	1.800	2.000	0.071	0.079
L		0.550 REF		0.022 REF
L1	0.300	0.500	0.012	0.020
θ	0 °	8 °	0 °	8 °
x		1.460 TYP		0.057 TYP
y		0.650 TYP		0.026 TYP
z		0.500 TYP		0.020 TYP

12.3 Flat TO-92 Package Information




Figure.15 Flat TO-92 Chip Marking Spec




Figure.16 Flat TO-92 Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	1.420	1.620	0.056	0.064
A1	0.660	0.860	0.026	0.034
b	0.350	0.480	0.013	0.019
b1	0.400	0.510	0.016	0.020
c	0.330	0.510	0.013	0.020
D	3.900	4.100	0.154	0.161
D1	2.280	2.680	0.090	0.106
E	3.050	3.250	0.120	0.128
e	1.270 TYP		0.050 TYP	
e1	2.440	2.640	0.096	0.104
L	14.350	14.750	0.565	0.581
θ	45 ° TYP		45 ° TYP	
x	2.025 TYP		0.080 TYP	
y	1.545 TYP		0.061 TYP	
z	0.500 TYP		0.020 TYP	

13 Copy Rights and Disclaimer

1. This document may not be reproduced or duplicated, in any form, in whole or in part without prior written consent of MagnTek . Copyrights © 2019, MagnTek Incorporated.

2. MagnTek reserves the right to make changes to the information published in this document at anytime without notice.

3. MagnTek’ s products are limited for use in normal commercial applications. MagnTek’ s products are not to be used in any device or system, including but not limited to medical life support equipment and system.

For the latest version of this document, please visit our website: www.magntek.com.cn