MT883X

RoHS

MagnTek | Now Part of NOVOSENSE


Omni-polar, Nano Power Hall-Effect Switch IC

1 Product Description

The MT883X family is produced with CMOS technology. The Hall IC internally includes high sensitivity horizontal hall plates, sleep/awake logics for mode control, a low-power on-chip oscillator, low noise analog signal chain with dynamic offset cancellation, hysteresis comparators and an output driver.

The product responds to either North pole or South pole magnetic fields. The output will be turned on (Low) when the magnetic flux density (B) is larger than the operating point (BOP), and be turned off (High) when the magnetic flux density (B) is lower than the releasing point (BRP).

The MT883X family provides a variety of packages to customers: DFN & SOT-23 for surface mount and flat TO-92 for through-hole mount. All packages are RoHS compliant.



2 Features

- CMOS Technology
- Omni-polar Switch
- 1.6～5V Operating Vcc Range
- -40℃~85℃ Operating Temperature
- Package Option:
  SOT-23
  Flat TO-92
  DFN1608
  DFN1616
- Magnetic Sensitivity Option:
  B_{OP}=±30Gs, B_{RP}=±20Gs
- Push Pull Output
- RoHS Compliant: (EU)2015/863

3 Product Overview of MT883X


Part No.	Description
MT8831A	Flat TO-92, bulk packaging (1000pcs/bag)
MT8831AT	SOT-23, tape & reel (3000pcs/bag)
MT8831DT-1608	DFN1608, tape & reel (10000pcs/bag)
MT8831DT-1616	DFN1616, tape & reel (3000pcs/bag)

4 Applications

- Home appliances, Industrial
- Position Detection
- Solid-State Switch
- Proximity Switch
- Smart Meter
- Handheld Device
- Consumer Device

5. Pin Configuration and Functions

	Vcc	Out	GND
SOT-23	1	2	3
Flat TO-92	1	3	2
DFN1608	3	2	1
DFN1616	4	5	2
Description	Power	Output Push Pull	Ground



深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com
微信扫码咨询客服

Table of Contents

1 Product Description....1
2 Features....1
3 Product Overview of MT883X....1
4 Applications....1
5 Pin Configuration and Functions....1
6 Definition of Switching Function....3
7 Function Description....3
8 Feature Description....3
9 Functional Block Diagram....4
10 Electrical and Magnetic Characteristics....4
10.1 Absolute Maximum Ratings....4
10.2 Electrical Specifications....5
10.3 Magnetic Characteristics....5
10.4 ESD Ratings....5
10.5 Characteristic Performance....6
10.6 Typical Output Waveform....7
11 Typical Application Circuit....7
12 Package Material Information....8
12.1 SOT-23 Package Information....8
12.2 Flat TO-92 Package Information....9
12.3 DFN1608 Package Information....10
12.4 DFN1616 Package Information....11
13 Copy Rights and Disclaimer....12

Reversion History

1	Originally Version	
2	1.1 Version	Update the Supply Voltage SPEC from 3.9V to 5V

深圳市满度科技有限公司
Tel:150-1290-5940
Web:www.manduic.com
Email:sales@manduic.com

6 Definition of Switching Function

Figure.2 shows the device functionality and hysteresis




Figure.2 Omni-polar Switching Function

7 Function Description

B_{OP}: Operating Point, Magnetic flux density applied on the branded side of the package which turns the output driver ON (V_{OUT}=Low)

B_{RP}: Releasing Point, Magnetic flux density applied on the branded side of the package which turns the output driver OFF (V_{OUT}=High)

B_{HYST}: Hysteresis Window, $|B_{OP} - B_{RP}|$
Devices that have a lower magnetic threshold (V_{OUT}=High) detect magnets at a farther distance. Higher thresholds (V_{OUT}=Low) generally require a closer distance or larger magnet.

8 Feature Description

The MT883X device is sensitive to the magnetic field component that is perpendicular to the top of the package




Figure.3 Flux Direction Polarity

9 Functional Block Diagram




Figure.4 Functional Block Diagram

10 Electrical and Magnetic Characteristics

10.1 Absolute Maximum Ratings

Absolute maximum ratings are limited values to be applied individually, and beyond which the serviceability of the circuit may be impaired. Functional operability is not necessarily implied. Exposure to absolute maximum rating conditions for an extended period of time may affect device reliability.

Symbol	Parameters	Min	Max	Units
V_{CC}	Supply Voltage	-	7	V
V_{RCC}	Reverse Battery Voltage	-0.5	-	V
V_{OUT}	Output Voltage	-	7	V
I_{OUT}	Continuous Output Current	-	3	mA
T_A	Operating Ambient Temperature	-40	85	℃
T_S	Storage Temperature	-50	150	℃
T_J	Junction Temperature	-	165	℃
B	Magnetic Flux Density	No Limit		Gs

10.2 Electrical Specifications

At T_A=-40~85℃, V_{CC}=1.6V~5V (unless otherwise specified)

Symbol	Parameters	Test Condition	Min	Typ	Max	Unit
V_{CC}	Supply Voltage	Operating	1.6	-	5	V
I_{CC}	Supply Current	V_{CC}=3.3V	-	1.7		uA
		V_{CC}=1.6V	-	1.0	-	uA
I_{AW}	Awake Current	V_{CC}=3.3V	-	2.5	-	mA
I_{SL}	Sleep Current	V_{CC}=3.3V	-	1.0	-	uA
V_{OL}	Output Low Voltage	I_{OUT}=1mA, |B| > |B_{OP}|	-	-	0.4	V
V_{OH}	Output High Voltage	I_{OUT}=1mA, |B| < |B_{RP}|	V_{CC}-0.4	-	-	V
F_{SW}	Switching Frequency	V_{CC}=3.3V	10	20	40	Hz
T_{AW}	Awake Time	V_{CC}=1.6V to 5V	6	10	24	us
T_{SL}	Sleep Time	V_{CC}=1.6V to 5V	25	50	105	ms
D.C.	Duty Cycle	V_{CC}=1.6V to 5V	-	0.02	-	%
T_{PO}	Power on Time	dVcc/dt>5V/us, |B| > |B_{OP}|	-	-	120	us
R_{TH}	Thermal Resistance of SOT-23		-	301	-	℃/W
	Thermal Resistance of DFN		-	301	-	℃/W
	Thermal Resistance of Flat TO-92		-	230	-	℃/W

10.3 Magnetic Characteristics

At V_{CC}=1.6V~5V (unless otherwise specified)

Part No.	Symbol	Min	Typ	Max	Unit
MT8831 Series	B_{OP}, T_A =25℃	±20	±30	±40	Gs
	B_{RP}, T_A =25℃	±10	±20	±30	Gs
	B_{HYST}, T_A =25℃	-	10	-	Gs

10.4 ESD Ratings

Symbol		Reference	Values	Unit
V_{ESD}	Human-body model (HBM)	AEC-Q100-002	±5000	V
	Charged-device model (CDM)	AEC-Q100-011	±1000	V

深圳市满度科技有限公司
Tel:150-1290-5940
Web:www.manduic.com
Email:sales@manduic.com

10.5 Characteristic Performance

At Vcc=3.3V




Figure.5 Supply Current vs. Temperature




Figure.6 Magnetic Characteristics vs. Temperature (BOP & BRP)




Figure.7 Magnetic Characteristics vs. Temperature (BHYST)

10.6 Typical Output Waveform

MT883XA as example




Figure.8 Digital Output vs. Magnetic Flux Density

11 Typical Application Circuit

MT883XAT as example




Figure.9 Typical Application Circuit

12 Package Material Information (For Reference Only – Not for Tooling Use)

12.1 SOT-23 Package Information




Figure.10 SOT-23 Chip Marking Spec




Figure.11 SOT-23 Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	1.050	1.300	0.041	0.051
A1	0.000	0.150	0.000	0.006
A2	1.000	1.200	0.039	0.047
b	0.300	0.500	0.012	0.020
c	0.080	0.220	0.003	0.009
D	2.800	3.020	0.110	0.119
E	1.500	1.700	0.059	0.067
E1	2.600	3.000	0.102	0.118
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0 °	8 °	0 °	8 °
x	1.460 TYP		0.057 TYP	
y	0.800 TYP		0.032 TYP	
z	0.600 TYP		0.024 TYP	

深圳市满度科技有限公司
Tel:150-1290-5940
Web:www.manduic.com
Email:sales@manduic.com

12.2 Flat TO-92 Package Information




Figure.12 Flat TO-92 Chip Marking Spec




Figure.13 Flat TO-92 Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	1.420	1.620	0.056	0.064
A1	0.660	0.910	0.026	0.036
b	0.330	0.560	0.013	0.022
b1	0.400	0.510	0.016	0.020
c	0.330	0.510	0.013	0.020
D	3.900	4.200	0.154	0.165
D1	2.280	2.680	0.090	0.106
E	2.900	3.280	0.114	0.128
e	1.270 TYP		0.050 TYP	
e1	2.440	2.640	0.096	0.104
L	13.500	16.200	0.531	0.638
θ	45 ° TYP		45 ° TYP	
x	2.025 TYP		0.080 TYP	
y	1.545 TYP		0.061 TYP	
z	0.500 TYP		0.020 TYP	

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

12.3 DFN1608 Package Information




Figure.14 DFN1608 Chip Marking Spec




Figure.15 DFN1608 Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.450	0.550	0.018	0.022
A1	0.000	0.050	0.000	0.002
A2		0.150 TYP		0.006 TYP
D	1.550	1.650	0.061	0.065
E	0.750	0.850	0.030	0.033
D1	0.580	0.680	0.023	0.027
E1	0.350	0.450	0.014	0.018
b	0.170	0.270	0.007	0.011
e		0.420 TYP		0.017 TYP
L	0.185	0.285	0.007	0.011

12.4 DFN1616 Package Information




Figure.16 DFN1616 Chip Marking Spec




Figure.17 DFN1616 Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.450	0.550	0.018	0.022
A1	0.000	0.050	0.000	0.002
A2		0.150 TYP		0.006 TYP
L	1.550	1.650	0.061	0.065
b	0.200	0.300	0.008	0.012
e		1.000 TYP		0.039 TYP

13 Copy Rights and Disclaimer

1. This document may not be reproduced or duplicated, in any form, in whole or in part without prior written consent of MagnTek . Copyrights © 2019, MagnTek Incorporated.

2. MagnTek reserves the right to make changes to the information published in this document at anytime without notice.

3. MagnTek’ s products are limited for use in normal commercial applications. MagnTek’ s products are not to be used in any device or system, including but not limited to medical life support equipment and system.

For the latest version of this document, please visit our website: www.magntek.com.cn

深圳市满度科技有限公司
Tel:150-1290-5940
Web:www.manduic.com
Email:sales@manduic.com